

## Mobile Prodima Mixer HLR-1200 (Re. 14-10186)

## Design:

- stainless steel DIN 1.4301 / AISI 304
- Capacity 1'100 litres Equipment:
- 2 high frequency knife heads, air protected shaft bearings.
- Lid of mixing tank with gas spring strut, 1 air outlet and 1 filling opening Ø 315mm
- Edge of tank with inserted seal made of silicone
- Drive to mixing screw with frequency invertor (for 11 kW)
- Mobile mixer
- Quickly dismountable mixing screw by pulling it out
- Air protected shaft bearings to mixing screw
- Mixing tank with flap, manual operation
- Tiltable mixing tank with lifting spindle and gear motor
- Surfaces in contact with the product : polished
- External surfaces : brushed
- Pneumatic service unit
- Stainless steel control cabinet, mobile, with remote control
- Mixer frame increased in height
- Dosing valve, mounted onto the outlet flap, manual operation

## Drives:

- Mixing screw 11 kW + forced ventilation 0,25 kW
- High frequency shear heads (knife heads)  $2 \times 5.5 \text{ kW}$
- Tilting system 1,1 kW

Power supply 63 A with CE-plug

Compressed air: 6 bar

Approx. dimensions: Length 315 cm, width 127 cm, H approx 202 cm (tank in horizontal position,

without air outlet)

Control cabinet approx. 60 x 100 x 120 cm

Weight: ca. 1000 kg

(Subject to changes without further notice)





Dismountable end shaft bearing mixing screw .Extraction mixing screw: by pulling it out